

Product Information

Mod.R&S 06 | Rev.4 | Update 02/2020 | Page 1




SPARKLE


Description PU based plotter cut heat transfer vinyl with smooth glitter surface and adhesive polyester backing. Excellent for multilayer application.

> Suitable for cotton, polyester, poly/cotton blends, elastic fabrics and spandex (not suited for treated and sublimated textiles).

- **Usage** Mirror cut the material
 - Place the material on the garment with its polyester backing
 - Heat apply at the conditions shown on the right
 - Remove the carrier warm

• Weed the exceeding material





Blade: 45° Pressure: 80 gf Speed: 25 cm/sec

Transfer settings

15 seconds at 155°C (311°F) medium pressure (3-4 bar)

Washing Wait at least 24 hours from application before washing. Washing resistance up to 80°C, best inside-out. Do not use bleach or other aggressive chemical agents. Suitable for dry cleaning. Suitable for tumble dry, cotton cycle.

> The product is REACH compliant The product is certified Öko-Tex® Standard 100 Class I The product is VEGANOK certified

Washing temperature



Dry cleaning



Tumble dryer









N.B. All information here contained are based on our experience.

We always recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight at temperatures between 65°F and 80°F



Management System ISO 9001:2015 ISO 14001:2015



The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance).

This document can be subject to variations. Updated versions are available on our website www.siser.com.

For further information, please contact our Sales Office.

